


Flared male thread connector



SAE 070120

Tube outer diameter		P-SAE/MS thread size	Basic order number	Size,mm		
in.	mm			L	E	F
1/8	3	5/16-24	-S-AN2ST5	26.9	1.6	11.1
3/16	4	3/8-24	-S-AN3ST6	27.9	3.2	12.7
1/4	6	7/16-20	-S-AN4ST7	31.2	4.4	14.3
1/4	6	1/2-20	-S-AN4ST8	31.2	4.4	15.9
1/4	6	9/16-18	-S-AN4ST9	33.0	4.4	17.5
1/4	6	3/4-16	-S-AN4ST12	34.8	4.4	22.2
5/16	8	1/2-20	-S-AN5ST8	31.2	6.0	15.9
3/8	10	9/16-18	-S-AN6ST9	33.0	7.5	17.5
3/8	10	3/4-16	-S-AN6ST12	35.1	7.5	22.2
3/8	10	7/8-14	-S-AN6ST14	38.1	7.5	25.4
1/2	12	9/16-18	-S-AN8ST9	36.6	7.5	20.6
1/2	12	3/4-16	-S-AN8ST12	37.6	9.9	22.2
1/2	12	7/8-14	-S-AN8ST14	40.6	9.9	25.4
1/2	12	1 1/16-12	-S-AN8ST17	44.7	9.9	31.8
5/8	16	3/4-16	-S-AN10ST12	40.6	10.7	23.8
5/8	16	7/8-14	-S-AN10ST14	43.2	12.3	25.4
5/8	16	1 1/16-12	-S-AN10ST17	47.2	12.3	31.8
3/4	18	3/4-16	-S-AN12ST12	45.2	10.7	28.6
3/4	18	7/8-14	-S-AN12ST14	46.4	12.7	28.6
3/4	18	1 1/16-12	-S-AN12ST17	50.0	15.5	31.8
3/4	18	1 5/16-12	-S-AN12ST21	50.8	15.5	38.1
7/8	22	1 3/16-12	-S-AN14ST19	50.5	18.3	34.9
7/8	22	1 5/16-12	-S-AN14ST21	51.3	18.3	38.1
1	25	1 1/16-12	-S-AN16ST17	51.1	16.7	34.9
1	25	1 3/16-12	-S-AN16ST19	51.8	18.3	34.9
1	25	1 5/16-12	-S-AN16ST21	51.8	21.5	38.1